

# 7026

## 26 litre Wide neck drum



For dimensional tolerances see table on next page

| Product part | Product code | Description             | Materials |
|--------------|--------------|-------------------------|-----------|
| Drum         | 7026B00-004  | 26 litre wide neck drum | HDPE      |
| Lid          | A7026-13-402 | Screw lid               | HDPE      |
| Gasket       | H14-306      | Sealing gasket          | EPDM      |

| Capacity    | Litres | US Gallons |
|-------------|--------|------------|
| Brimful     | 26.5   | 7          |
| When closed | 26     | 6.9        |

| Weight | Grams | Ounces |
|--------|-------|--------|
| Drum   | 920   | 32.45  |
| Lid    | 258   | 9.10   |
| Gasket | 15    | 0.53   |
| Total  | 1193  | 42.08  |

| Colours   | Colour code | PMS references |
|-----------|-------------|----------------|
| Container | White 004   | /              |
| Lid       | Red 402     | 199 C          |

| Hazardous material information |                               |
|--------------------------------|-------------------------------|
| Hazardous material type        | Solids                        |
| Packaging group                | I – II – III                  |
| UN marking                     | UN/1H2/X33/S/--/NL/CURTEC 874 |
| Maximum gross mass (kg)        | X=33                          |

| Product identification       | Drum      | Lid    |
|------------------------------|-----------|--------|
| Manufacturer ID              | Bottom    | --     |
| Country of origin            | Bottom    | --     |
| Product code                 | Bottom    | --     |
| Recycle logo / Material type | Bottom    | Inside |
| Date clock                   | Bottom    | Inside |
| UN-mark                      | Side wall | --     |
| Food logo                    | Bottom    | --     |
| Material track clock         | Bottom    | --     |

| Other information                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Maximum filling temperature is 70°C/ 158°F</p> <p>Contents must have cooled to 30°C/ 86°F before containers can be closed and stacked</p> <p>DoC available on request</p> <p>UN certificate available on request</p> <p>MVTR declaration available on request</p> <p>Watertightness declaration available on request</p> <p>Other colours available on request</p> <p>User manual available on request</p> |

| Wall thickness         | mm   |
|------------------------|------|
| Minimal wall thickness | ≥1.5 |
| Nominal wall thickness | ≥1.6 |

| Dimensional tolerances | %    |
|------------------------|------|
| Height                 | ±2.5 |
| Diameter               | ±1.5 |

| Weight tolerance                                                                        |
|-----------------------------------------------------------------------------------------|
| All products have a tolerance of ±4% on the initial weight mentioned on this data sheet |

© 2016 Property of CurTec International B.V. All rights explicitly reserved, it is not allowed to copy or communicate to other parties without written consent of CurTec.